HTG fiberglass sleeve

1.Product Introduction

ZBAO HTG Fiberglass Sleeve is kind of insulation fire sleeve, which braided by E grade glass fiber then weave lock by impregnated with special resin. Widely used to protect wires from high temperature and occasional flame on electric motor, household appliances and automobile.

2.Product Characters

Thermal Class	C
Size/Inner diameter	1mm-30mm
Colour	White.Other colors can be customized
Working temperature	-70°C -550°C
Breakdown voltage	1kv
Character	High temperature & flame resistant,anti-aging,acid and alkali resistant.

3.Standard Specifications

ZBAO Part No.	Inner Dia./mm		Thickness /mm	Roll Length/m
	Nominal	Tolerance		
ZBHTG-S-010	1	+0.30 -0.0	0.30±0.12	Min Packing 100m/roll MOQ:5000m
ZBHTG-S-015	1.5			
ZBHTG-S-020	2		0.35±0.15	
ZBHTG-S-025	2.5			
ZBHTG-S-030	3			Min Packing 100m/roll MOQ:3000m
ZBHTG-S-040	4			
ZBHTG-S-050	5	+0.5 -0.0	0.38±0.15	
ZBHTG-S-060	6			
ZBHTG-S-070	7			
ZBHTG-S-080	8			
ZBHTG-S-090	9	+1.0 -0.0	0.40±0.20	
ZBHTG-S-100	10			Min Packing
ZBHTG-S-120	12			50m/roll MOQ:2000m
ZBHTG-S-130	13			
ZBHTG-S-140	14			Min Packing 25m/roll MOQ:1000m
ZBHTG-S-160	16			
HTHTG-S-180	18	+2.0 -0.0	0.45±0.22	Min Packing 20m/roll MOQ:1000m
HTHTG-S-200	20			
HTHTG-S-220	22			
HTHTG-S-250	25			Min Packing 20m/roll MOQ:1000m



